



TECHNICAL DATA SHEET

AKVAKOL 100.1

| | |
|------------------------------|---|
| Product type | Modified water-soluble glue based on synthetic polymers, fillers, thickeners, stabilizers and preserving additives. |
| Application area | Production of cardboard tubes, edge protectors and packaging, binding cardboard, paper bags and other products made of paper and cardboard. Adhesive is used both for the current application method, nozzle and immersion, suitable for application by a roller and a disk. |
| Technical parameters | |
| Appearance | Dispersion, color white to light-beige |
| Viscosity | 3.000 -4.000 mPa.s |
| pH level | 3,0 - 5,0 |
| Solid content | 35-37% |
| Operating temperature | Fast setting. Non-toxic, short fixation time and high-quality impregnation onto a cardboard layer. Adhesive joint is resistant to external factors. To achieve the required working viscosity of the adhesive, it is possible to dilute it with water. The dilution ratio is determined in a practical way in each specific case. |
| Handling | Optimum temperature of use 15-40 °C |
| Shelf life | In closed buckets 6 months from the date of production |
| Storage | Optimum storage temperature 5-25 °C, protect from frost |

For further information,
please, contact our adhesive compositions sales department:
Tel. +38044 501 13 76, +38044 507 11 57